

What it's made of makes all the difference.



Release the natural power of stone to enrich modern living.



Fire Resistant

ROCKWOOL stone wool insulation will not burn or produce smoke and can withstand temperatures up to 2150°F (1177°C). It can help protect occupants and reduce property damage.



Water Repellent

ROCKWOOL stone wool insulation repels water so its R-value is not comprised by moisture or water. It also contributes to a healthy indoor environment because of its resistance to rot, mildew, mold and bacterial growth.



Thermal Resistance

ROCKWOOL insulation products make living conditions more healthy and comfortable. Thermal resistance can dramatically reduce heating, cooling, and ventilation costs, and reduce a home's carbon footprint.



Sound Absorbent

ROCKWOOL stone wool helps absorb sound and reduces sound transmissions. This enables productivity in the workplace, and helps to keep homes quiet and comfortable.



Comfortboard® 80
Exterior non-structural insulated sheathing boards used as continuous insulation



Comfortbatt®
Semi-rigid thermal batt insulation designed for exterior studs



Safe'n'Sound®
Premium fire and soundproofing insulation for interior walls and ceilings between floors

Safe'n'Sound®

Fire & soundproofing insulation



Stud type	Thickness	Width	Length	Coverage**
16" Wood	3 in.	15 1/4 in.	47 in.	59.7 ft. ²
16" Wood	6 in.	15 1/4 in.	47 in.	29.87 ft. ²
19.2" Wood	6 in.	19 1/5 in.	47 in.)	31.33 ft. ²
24" Wood	3 in.	23 in.	47 in.	60.1 ft. ²
24" Wood	6 in.	23 in.	47 in.	30.03 ft. ²
16" Steel	3 in.	16 1/4 in.	48 in.	64 ft. ²
24" Steel	3 in.	24 1/4 in.	48 in.	64 ft. ²
16" I-Joist	6 in.	16 1/4 in.	48 in.	32.5 ft. ²
19.2" I-Joist	3 in.	19 1/5 in.	47 in.	62.7 ft. ²

Comfortboard® 80

Continuous insulation



R-Value*	Thickness	Width	Length	Coverage**
R4.2	1 in.	24 in.	48 in.	80 ft. ²
R5.3	1 1/4 in.	24 in.	48 in.	56 ft. ²
R5.3	1 1/4 in.	48 in.	96 in.	1024 ft. ²
R6.3	1 1/2 in.	24 in.	48 in.	48 ft. ²
R6.3	1 1/2 in.	48 in.	72 in.	672 ft. ²
R6.3	1 1/2 in.	48 in.	96 in.	896 ft. ²
R8.4	2 in.	24 in.	48 in.	40 ft. ²
R8.4	2 in.	48 in.	96 in.	640 ft. ²
R10.5	2 1/2 in.	24 in.	48 in.	32 ft. ²
R10.5	2 1/2 in.	48 in.	72 in.	384 ft. ²
R10.5	2 1/2 in.	48 in.	96 in.	576 ft. ²
R12.6	3 in.	24 in.	48 in.	24 ft. ²
R12.6	3 in.	48 in.	96 in.	480 ft. ²
R16.8	4 in.	24 in.	48 in.	16 ft. ²
R21	5 in.	24 in.	48 in.	16 ft. ²

*Limited availability PNW


**coverage based on sq. ft per pack or pallet based on packaging configuration

Comfortbatt®

Thermal batt insulation



R-Value*	On Center	Thickness	Width	Length	Coverage**
Wood Stud					
R13	16"	3 1/2 in.	47 in.	15 1/4 in.	59.7 ft. ²
R13	24"	3 1/2 in.	47 in.	23 in.	60.1 ft. ²
R15	16"	3 1/2 in.	47 in.	15 1/4 in.	59.7 ft. ²
R15	24"	3 1/2 in.	47 in.	23 in.	61.1 ft. ²
R21	16"	5 1/2 in.	47 in.	15 1/4 in.	39.8 ft. ²
R21	24"	5 1/2 in.	47 in.	23 in.	37.5 ft. ²
R23	16"	5 1/2 in.	47 in.	15 1/4 in.	39.8 ft. ²
R23	24"	5 1/2 in.	47 in.	23 in.	37.5 ft. ²
R30	16"	7 1/4 in.	47 in.	15 1/4 in.	29.9 ft. ²
R30	24"	7 1/4 in.	47 in.	23 in.	30.7 ft. ²
R38	16"	9 1/2 in.	47 in.	15 1/4 in.	19.9 ft. ²
R38	24"	9 1/2 in.	47 in.	23 in.	22.5 ft. ²
Steel Stud					
R10	16"	2 1/2 in.	48 in.	16 1/4 in.	86.7 ft. ²
R15	16"	3 1/2 in.	48 in.	16 1/4 in.	65 ft. ²
R15	24"	3 1/2 in.	48 in.	24 1/4 in.	64.7 ft. ²
R24	16"	6 in.	48 in.	16 1/4 in.	43.3 ft. ²
R24	24"	6 in.	48 in.	24 1/4 in.	40.4 ft. ²
R30	16"	7 1/4 in.	48 in.	16 1/4 in.	32.5 ft
R32	16"	8 in.	48 in.	16 1/4 in.	32.5 ft



Please check with ROCKWOOL™ Customer Service for minimum order quantities. For custom sizes, please contact your ROCKWOOL Sales representative.

ROCKWOOL
8024 Esquesing Line
Milton, ON L9T 6W3
Tel: 1 800 265 6878
rockwool.com



2021 Fine Homebuilding House*
Jason Mollak, JPM Construction - Nebraska

ROCKWOOL™ Stone Wool Insulation Applications



Comfortboard® 80
Exterior non-structural insulated sheathing boards used as continuous insulation

- 1 Below Grade - Foundation continuous insulation
- 2 Below Grade - Underslab continuous insulation
- 3 Above Grade - Continuous exterior wall insulation



Comfortbatt®
Semi-rigid thermal batt insulation designed for exterior studs

- 4 Above Grade - Exterior wall cavity
- 5 Basement - Exterior wall cavity
- 6 Attic/Cathedral Ceiling - Conditioned & unconditioned



Safe'n'Sound®
Premium fire and soundproofing insulation for interior walls and ceilings between floors

- 7 Interior wall cavity - Sound dampening batts
- 8 Floors/Ceiling - Sound dampening batts

* Some modifications made for illustrative purposes. Original Render: Design Level 4 Modifications: First Floor Media+Design Inc.